

An application of the catastrophe theory to building the model of elastic-plastic behaviour of materials.

Part 1. Uniaxial deformation (stress)

L. N. Maurin, I. S. Tikhomirova ¹

*Physics Department, Ivanovo State University
Ermaka St. 39, Ivanovo, 153025, Russia*

Abstract

The uniaxial elastic-plastic deformation process is considered. Mathematical model of this process was built. According to this model all stable static states form the lattice, which is called the Δ -lattice.

The idea suggested in [1, 2] will be evolved into this and latter papers. The idea consist in definition of variety of elastic-plastic states seen in plastic deformation process. The catastrophe theory underlies this approach to the problem. As it is known, the subject of the catastrophe theory is an investigation of qualitative character of the equation solutions in dependence on the parameters, which are presented in this equations. In this article we study the elastic-plastic deformation from standpoint of equilibrium.

There are various models in the plasticity theory, which are able to describe plastic behavior of materials. But all these models are considering materials with smooth deformation diagram (fig. 1a). Nevertheless there exist broken deformation curves, which are typical for serrated yielding or the Portevin Le-Chatelier effect (see figure 1b). The classical plasticity theory has no mathematical models describing such a behaviour in deformation process.

In this article we will try to build macroscopic model of elastic-plastic behaviour of bodies under loading. We take into account the assumption of existence of the equilibrium static states of the deforming material. These equilibrium states are elastic states. Plastic states are not static equilibrium. They are implemented in the transforming from one equilibrium state (elastic state) to another. Thus we can construct the variety of equilibrium states that is depicted on fig. 2 for ideal plastic materials. As it is seen from fig. 2 the variety of stable states is the lattice which we will call the Δ -lattice, here stress is non-dimensional quantity, i. e. $\sigma = \sigma/E$, where E is the Young's modulus.

¹e-mail: tihomir@ivanovo.ac.ru

Let us consider the deformation process now. Firstly, the deformation of the material is elastic (see the rod O_0A_0 on fig. 2). Hook's law carries into effect, i. e. $\sigma = \varepsilon$, where σ is the non-dimensional stress, ε is the strain. The point A_0 is the last point of elastic states on the first rod of the Δ -lattice. The elastic branch O_0A_0 doesn't exist over this point (i. e. for $\varepsilon \not\leq \varepsilon_{A_0}$). As soon as deformation ε is greater than ε_{A_0} there will be a jump to another equilibrium branch O_1A_1 . Further, as the strain ε exceeds value ε_{A_1} the new jump on the branch O_2A_2 will take place etc. Thus the plastic deformation process is spasmodic, i. e. increase of plastic deformation value is accomplished by jumps and is not smooth.

As it was said before we wish to use the catastrophe theory to build the mathematical model of elastic plastic deformation. Everyone knows that the investigation of the potential function (or the function of state) underlies the catastrophe theory. That is why we must construct this function. The function of state have to be minimum for each stable state. Consequently the function of state is minimum on the rods of Δ -lattice. Since the minima of smooth function are to be separated by maximum then unstable states must exist between the rods of Δ -lattice. That is why the Δ -lattice depicted on fig. 2 is required in additional constructions. They are the joining the upper end (A_i) of each rod with lower end (O_{i+1}) of the next rod of Δ -lattice (dotted lines on fig. 3). The function of state is maximum for each point of the dotted lines, i. e. these states are unstable. The unstable states form another lattice, which will be called additional variety.

Everything we need now is done and we can build the function of state. But before it we must discuss the question of parameters. That means that we will discuss the possible geometry of jumps. At first we consider the model with parameter σ , i. e. stress is externally changed in experiments. In this case it can be realized only the following types of jumps (see fig. 4). First one is an "ideal" jump, when the stress is constant and equal σ^* , elastic strain is constant as well (see the change $A \rightarrow B$ on fig. 4). We must emphasize that the total strain is increasing. The second passage is the passage $A \rightarrow B_1$ (see fig. 4) with increasing stress σ and strain ε . The jump with decreasing stress σ from point A can not be realized because when stress is decreased the elastic unloading will be realized (branch AO on fig. 4).

Now we will consider experiments with external changing parameter ε (hard loading device as an example). In this case the "ideal" jump is $A \rightarrow B$ (see fig. 5) with constant strain ε and decreasing stress σ . Another possible passage in the model with external parameter ε is the passage at increasing

strain ε and decreasing stress σ (see the passage $A \rightarrow B_1$ on fig. 5). Also we suppose that the jump at constant stress and increasing strain ($A \rightarrow B_2$ at fig. 5) can be implemented under definite conditions.

Another type of passages, namely the passages at increasing stress and strain ($A \rightarrow B_3$ on fig. 5) and the passages at decreasing stress and strain, cannot be realized in the model with parameter ε .

Now we will consider experiments with external changing parameter ε (hard loading device as an example). In this case the “ideal” jump is $A \rightarrow B$ (see fig. 5) with constant strain ε and decreasing stress σ . Another possible passage in the model with external parameter ε is the passage at increasing strain ε and decreasing stress σ (see the passage $A \rightarrow B_1$ on fig. 5). Also we suppose that the jump at constant stress and increasing strain ($A \rightarrow B_2$ at fig. 5) can be implemented under definite conditions.

Another type of passages, namely the passages at increasing stress and strain ($A \rightarrow B_3$ on fig. 5) and the passages at decreasing stress and strain, cannot be realized in the model with parameter ε .

In accordance with geometry of jumps offered above we can distinguish two types of state functions. The first one is the state function with parameter σ , and the second one is the state function with parameter ε .

Let us summarize the demands that the state function have to satisfy. The state function must be smooth and has minima on every rod of Δ -lattice and maxima for rods of additional variety. In accordance with these demands we start to construct the state functions. Firstly we consider the state function with parameter σ . The function looks like this:

- (1) $\Phi = \Phi_n(\varepsilon; \sigma),$
- (2a) $\Phi'_n \equiv \frac{d\Phi_n}{d\varepsilon} = - \prod_{s=-k}^k (\sigma - \varphi_{n-s}(\varepsilon)),$
- (2b) $\varepsilon_i \leq \varepsilon < \varepsilon_{i+1}$, if ε_i – projection of lower end of rod onto ε axis,
 ε_{i+1} – projection of lower end of next rod onto ε axis;
- (2c) $\varepsilon_i \leq \varepsilon \leq \varepsilon_{i+1}$, if ε_i – projection of lower end of rod onto ε axis,
 ε_{i+1} – projection of upper end of rod onto ε axis that is defined
 by function φ_l , where $l < i$;
- (2d) $\varepsilon_i < \varepsilon < \varepsilon_{i+1}$, if ε_i – projection of upper end of rod onto ε
 axis,
 ε_{i+1} – projection of lower end of next rod onto ε axis;
- (2e) $\varepsilon_i < \varepsilon \leq \varepsilon_{i+1}$, if ε_i – projection of upper end of rod onto ε
 axis,
 ε_{i+1} – projection of upper end of next rod onto ε axis;

(3) $\Phi_n(\varepsilon_{n+1}) = \Phi_{n+1}(\varepsilon_{n+1})$ – lacing condition,
 where $n < (N - 1)$, N – number of intervals on ε axis.
 Here for rods of Δ -lattice

$$(4) \quad i = 2m, \varphi_i(\varepsilon) = \varepsilon - \sum_{l=0}^{\frac{i}{2}-1} \Delta_l,$$

and for rods of additional variety

$$(5) \quad i = 2 \cdot m + 1, \quad \varphi_i(\varepsilon) = k_i \cdot \left(\varepsilon - \sum_{l=0}^{\frac{i-1}{2}} \Delta_l \right),$$

where $k_i = \frac{\left(\varepsilon - \sum_{i=0}^{m-1} \Delta_l \right)}{\left(\varepsilon - \sum_{i=0}^m \Delta_l \right)} = 1 + \frac{\Delta_m}{\varepsilon - \sum_{i=0}^m \Delta_l}$, and ε is equal to the strain in point A_m .

As it is seen from equations (1) – (3) the state function is constructed of all $\varphi_i(\varepsilon)$ existing on the examining part of the strain axis ε . It is not difficult to test (using (1) – (5)) that the state function Φ_n is minimum on all rods of Δ -lattice (i. e. these states are stable) and maximum on all rods of additional variety (unstable states). It is necessary to notice that the end points of rods are degenerated critical points.

The second state function type is the state function with parameter ε . We define this function as:

$$(6) \quad \Phi = \Phi_n(\sigma; \varepsilon), \quad \Phi_n(\sigma_{n+1}) = \Phi_{n+1}(\sigma_{n+1}),$$

$$(7) \quad \Phi'_n = \frac{d\Phi_n}{d\sigma} = - \prod_{i=2n}^{2(N-1)} (\varepsilon - \psi_i(\sigma)) = \prod_{i=2n}^{2(N-1)} (\psi_i(\sigma) - \varepsilon),$$

defined for region $\sigma_n < \sigma \leq \sigma_{n+1}$, if $n \neq 0$,

and for $\sigma_n \leq \sigma \leq \sigma_{n+1}$, if $n = 0$, here N stands for number of rods of Δ -lattice.

And $\psi_i(\sigma) = \sigma + \sum_{l=0}^{\frac{i}{2}-1} \Delta_l$, for the rods of Δ -lattice, where $i = 2m$,

for the rods of additional variety $\psi_i(\sigma) = \frac{1}{k_i} \cdot \sigma + \sum_{l=0}^{\frac{i-1}{2}} \Delta_l$, where $i = 2 \cdot m + 1$.

Here k_i is the same as in the case of a model with parameter σ .

Like the previous state function (with parameter σ) this one is formed by means of all functions $\psi_i(\sigma)$ existing on the examining part of the stress axis σ , i. e. it is formed by means of all rods of Δ -lattice and additional variety existing on the examining part of the σ -axis. It is easy to verify that the state function $\Phi_n(\sigma; \varepsilon)$ (see (6) – (7)) also satisfies the above demands.

In conclusion we emphasize that in accordance with our point of view the continuous deformation curve must be replaced by Δ -lattice (fig. 6). Only the points of Δ -lattice are the static stable states here. There are no static stable states between the rods of Δ -lattice (for instance, points C, D, E, F, J on fig. 6).

So the state function was build for the macroscopic models of elastic-plastic deformation both with parameters ε and σ .

References

- [1] Maurin L. N. The lattice as the form of multitude of elastic-plastic states of medium. Part 1. Macroscopic quantization of plasticity in the uniaxial deformation. Vestnik Ivanovsk. Gosudarstven. Universiteta. Seria Biologia, chimia, fizika, matematika. 2000. Vip. 3. C. 76-82 (Russian)
- [2] Maurin L. N., Tikhomirova I. S. The lattice as the form of multitude of elastic-plastic states of medium. Part 2. The model containing the similarity hypothesis. Vestnik Ivanovsk. Gosudarstven. Universiteta. Seria Biologia, chimia, fizika, matematika. 2000. Vip. 3. C. 82-84 (Russian)

Fig. 1 a, b: a – smooth deformation curve; b – deformation curves $\sigma(\varepsilon)$ of pressing of nanocrystal (1) and monocrystal (2) niobium.

Fig. 2. The Δ -lattice of ideal plastic body.

Fig. 3. The Δ -lattice and additional variety of ideal plastic material.

Fig. 4. The possible transitions in the model with parameter σ .

Fig. 5. Possible (AB, AB₁, AB₂) and impossible (AB₃) transitions in the model with parameter ε .

Fig. 6. Replacement of continuous deformation curve by Δ -lattice.

This figure "Pict_1.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>

This figure "Pict_2.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>

This figure "Pict_3.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>

This figure "Pict_4.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>

This figure "Pict_5.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>

This figure "Pict_6.gif" is available in "gif" format from:

<http://arXiv.org/ps/cond-mat/0111304v1>